

MSDS P201  
REV. # 1  
REV. DATE: April 9, 2010

## Material Safety Data Sheet

### **Section 1. Chemical Product and Company Identification**

Product Name: P2AO201 Oil  
Synonyms: Synthetic Polyalphaolefin mixture  
Product Use: Synthetic Sintered metal and sleeve bearing Lubricant

Supplier / Manufacturer:

**Permawick Company**  
**255 E. Brown Street**  
**Suite 100**  
**Birmingham, Michigan 48009**  
**Tel : (248) 433-3500 Fax: (248) 433-1824**

#### **Emergency Phone Numbers:**

Monday - Friday, 8 am -4:30 pm (EST): (812) 376-0703  
Chemtrec 24 hr. : (800) 424-9300 (US and Canada)

#### **Information Contacts :**

For technical information contact your sales representative.

### **Section 2. Composition / Information on Ingredients**

#### ***Criteria for Listing Components in the Composition Section:***

- \* Carcinogens are listed at 0.1 % or greater.
- \* Components considered hazardous by OSHA are listed at 1.0 % or greater.
- \* Non-hazardous components present at 3.0 % or greater.

This is not intended to be a complete compositional disclosure.

#### **Hazardous classification:**

		<u>CASRN</u>	<u>Percent (by wt.)</u>	<u>HAZARD</u>
1.	1-Decene, Homopolymer, Hydrogenated	68037-01-4	94.0 + %	none noted
2.	Anti-oxidant		0.99 - 2.00 %	non noted
3.	Mineral Oil mixture	*****	0.99 - 5.00 %	none noted

\* See section 8 for Exposure Guidelines \*

### **Section 3. Hazards Identification**

#### **\*\*\*\*Emergency Overview\*\*\*\***

This compound is not an acute or physical hazard under normal conditions of use. However, inhalation of oil mist or vapors at elevated temperatures may cause respiratory irritation. Harmful if aspirated into lungs.

MSDS P201

REV. # 1

REV. DATE: April 9, 2010

***Potential Health Effects, Signs and Symptoms of Exposure:***

Inhalation: Irritation possible. Fumes from heated material may cause irritation. Sprays or mists may be irritating to the upper respiratory tract.

Ingestion: May cause gastrointestinal irritation. Harmful if aspirated into lungs.

Eye Contact: Irritating. May cause tearing, reddening, or swelling.

Skin Contact: Prolonged or repeated contact may result in defatting, and / or drying of the skin which may lead to skin irritation and dermatitis, and may cause allergic skin reactions.

Other chronic effects: Refer to Section 11, Toxicological Information for details.

**Section 4. First Aid Measures**

***FIRST AID***

Eye Contact: Immediately flush eyes with plenty of water. Hold eyelids apart for at least 15 minutes with running water. If irritation develops or persists seek medical attention immediately.

Ingestion: If victim is alert give 3 - 4 glasses water to drink to dilute the product. DO NOT induce vomiting. Do not give anything by mouth to an unconscious or convulsing person.

Inhalation: Immediately remove victim to fresh air. Get medical attention immediately if respiratory irritation develops or if breathing becomes difficult.

Skin Contact: Wash affected area immediately with soap and plenty of water. Remove contaminated clothing and wash or discard clothing before reuse. If symptoms occur obtain medical attention immediately.

Medical Conditions Aggravated by Exposure:

Existing chronic respiratory problems such as asthma, emphysema, or bronchitis. Preexisting skin conditions, allergies and eczema. Treat symptomatically.

**Section 5. Fire Fighting Measures**

Flash Point :	230° C	Method used:	ASTM D92
Autoignition Point:	not determined	Flammability Classification:	not flammable
Lower explosive limit:	not available	Upper explosive limit:	not available
NFPA rating:	none		

***Other Flammable Properties:***

Can burn in a fire and form carbon dioxide and some carbon monoxide. Decomposition and combustion products may be formed from phosphorus oxides.

***Extinguishing Media:***

MSDS P201

REV. # 1

REV. DATE: April 9, 2010

Water mist or fog, agents approved for Class B hazards (e.g. dry chemical, carbon dioxide, foam, steam). Water or foam may cause frothing.

***Fire Fighting Precautions and Procedure:***

Firefighters should wear self - contained breathing apparatus (MSHA/NIOSHA) approved or equivalent) in the positive - pressure mode with full protective gear especially when there is a possibility of exposure to smoke, fumes, or hazardous decomposition of products. Carefully cool with water spray. The cool water spray application has frequently been used with success in extinguishing such fires by causing the frothing to occur only on the surface and this foaming action blankets and extinguishes the fire. (NFPA 325M - 1984)  
Containers can build up pressure if exposed to heat (fire). Cool with water spray.

**Section 6. Accidental Release Measures**

***Spill or Release Procedures:***

Ventilate area. Prevent spreading by diking or ditching. Absorb spill with inert material and place in appropriate chemical waste container. Obey any federal, state, and local laws and regulations. Do not flush into sewers discharging into domestic water systems or natural waterways. Use personal protective equipment (Sec.8). Spilled material will cause a slippery surface. Avoid trips and falls.

**Section 7. Handling and Storage**

Handling: Thoroughly wash after handling and before eating, drinking, or using tobacco products. Use adequate ventilation and avoid breathing vapor or mist. Avoid contact with eyes, skin, clothing. Avoid ingestion.

Storage: Keep container tightly closed when not in use and during transport. Store under dry conditions and at temperatures between 10°C and 50°C.

**Section 8. Exposure Controls / Personal Protection**

Exposure Limits:

<u>Component Information</u>		<u>OSHA</u>		PEL	<u>ACGIH</u>	
No.	Units	TWA	STEL		TWAS	STEL
1.	mg/m <sup>3</sup>	none	established		none	established
2.	mg/m <sup>3</sup>	none	established	5	none	established
3.	mg/m <sup>3</sup>	none	established		none	established

Carcinogens:

IARC: None

NTP: None

OSHA: None

**Engineering Controls:** Adequate ventilation must be provided.

***Personal Protective Equipment:***

Eye / Face Protection: Use chemical splash goggles

MSDS P201

REV. # 1

REV. DATE: April 9, 2010

Skin Protection:

Wear impermeable gloves to minimize skin contact.

Respiratory Protection:

Where exposure is likely to exceed acceptable criteria, use NIOSH/ OSHA approved respiratory equipment. Respirators should be selected based on the form and concentration of contaminant in air with OSHA concentration of contaminant in air and in accordance with OSHA (29 CFR 1910.134).

***Other Protective Equipment:***

In order to identify additional Personal Protective Equipment requirements, the recommendation is made that a hazard assessment in accordance with the OSHA PPE Standard ( 29 CFR 1910.132) be conducted before product use.

**Work Practice Controls:**

1. Wash exposed skin promptly to remove any material.
2. Wash hands and face before consuming food , drinking, or before using tobacco products.
3. Do not store food, drink, nor tobacco products in the same area where the product is stored.

**Section 9. Physical and Chemical Properties**

Boiling Point:	Not determined
Pour Point:	< 60° C (ASTM D-97)
Vapor Pressure:	< 1 mm Hg @ 300° F
Vapor Density (Air = 1):	heavier than air
Specific Gravity:	0.952 @ 60 / 60° F
Density:	see specific gravity
pH:	Not available
Viscosity	46cSt @ 40° C
Evaporation Rate:	slower than Butyl Acetate
Solubility in water:	Negligible
Appearance and color:	Yellow, Translucent
Odor:	odorless

**Section 10. Stability and Reactivity**

Stability:	Stable under normal storage conditions.
Hazardous Polymerization:	Will not occur during normal conditions.
Conditions to avoid:	Temperature conditions which induce thermal decomposition.
Material Incompatibility:	Avoid oxidizing agents, strong acids, strong bases.
Hazardous Decomposition Products:	Carbon dioxide, carbon monoxide, nitrogen, phosphorus oxides, and other toxic compounds.

**Section 11. Toxicological Properties**

Inhalation: No test data found on this product.

Ingestion: No test data found on this product.

MSDS P201  
REV. # 1  
REV. DATE: April 9, 2010

Eye Contact: Rabbit - slight irritation.

Skin Contact: Rabbit - irritant.

Chronic Toxicity: No component of this product present at levels greater than 0.1% is identified as a carcinogen by the U.S. National Toxicology Program, the U.S. Occupational Safety and Health Act, or the International Agency on Research on Cancer (IARC).

Other Toxicological Information: None available

## **Section 12. Ecological Information**

Ecological Fate: No data available

Environmental Effects:

Acute Toxicity to Fish:

96 hr LC50 ( Rainbow Trout ) = 0.75 mg / l

96 hr LC50 ( Fathead Minnow ) = 100 mg / l

Acute Toxicity to Invertebrates:

48 hr LC50 ( Daphnia Magna ) = 0.27 mg / l

## **Section 13. Disposal Considerations**

Disposal Method: All recovered material should be packaged, labelled, transported, and disposed or reclaimed in accordance with federal, state and local regulations. Incineration is the preferred method. Reclaim where possible.

EPA Hazardous Waste: None

## **Section 14. Transportation Information**

U.S. Department of Transportation:

DOT proper shipping name: not regulated

DOT classification: not regulated

## **Section 15. Regulatory Information**

### **U.S. Federal Regulations**

OSHA: Preparation of this document is in accordance with the MSDS requirements of the OSHA Hazard Communication Standard.

SARA Section 302:

This product contains no chemicals regulated under Section 302 as extremely hazardous substances.

SARA Section 311 / 312: Hazard classification: none noted

MSDS P201  
REV. # 1  
REV. DATE: April 9, 2010

SARA Section 313:

This product contains no chemical requiring annual Toxic Chemical Release Reporting under Section 313.

TSCA:

Section 8 (b) - Inventory: All functional components of this product are listed in the TSCA inventory.

Section 12 (b): Export Notification:

This product does not contain any substances subject to export notification under Section 12 (b) of TSCA.

CERCLA Hazardous Materials: None

RCRA: This product is not considered to be hazardous waste under RCRA (40 CFR 261).

AICS: Australian Inventory:

This product contains only chemicals which are currently listed on the Australian Inventory of Chemical Substances.

CDSL: Canadian Inventory-

All the chemicals in this product are listed on the DSL.

EINECS: European Inventory-

All the chemicals in this product are listed on the European Inventory of Existing Commercial Chemical Substances.

MITI: Japanese Inventory:

All the chemicals in this product are listed on the Japanese Ministry of International Trade and Industry List of Existing and New Chemical Substances.

KCSL: Korean Inventory:

This product only contains chemicals which are currently listed on the Korean Chemical Substances List.

PICCS: Philippine Inventory:

Not determined.

### **State Regulations**

#### ***California Proposition 65:***

This product is not known to contain any chemicals known to the state of California to cause cancer or birth defects. However, we do not conduct routine analysis for all listed materials.

### **US Federal Regulations:**

#### ***Clean AIR ACT: ODS -***

This product neither contains, nor was manufactured with, a Class I or Class II ozone depleting substance (ODS). We have relied on our suppliers labeling their products. None have done so.

### **Section 16. Other Information**

MSDS P201  
REV. # 1  
REV. DATE: April 9, 2010

HMIS Rating System: Health = 1 Flammability = 1 Reactivity = 0  
Ratings key: 4 = Highest hazard , 0 = Lowest hazard, \* = Chronic Health Hazard

Revision summary:

This is the first issue of this MSDS in the ANSI Z400.1 - 1993 format  
Approval date : 01/24/97  
Supersedes: 09/01/89

This information presented herein is believed to be factual as it has been derived from works and opinions of persons believed to be qualified experts; however, nothing contained in this information is to be taken as warranty or representation for which Permawick bears legal responsibility. Any recommendations should be reviewed by the user in the specific context of the intended use to determine whether they are appropriate.

ACGIH: American Conference of Governmental Industrial Hygienists  
ANSI: American National Standards Institute  
CERCLA: Comprehensive Emergency Response, Compensation and Liability Act  
HMIS: Hazardous Materials Identification System  
IARC: International Agency for Research on Cancer  
OSHA: Occupational Health and Safety Administration  
NTP: National Toxicology Program  
PEL: OSHA Permissible Exposure Limit  
RCRA: Resource Conservation and Recovery Act  
SARA: Superfund /amendment Reauthorization Act  
STEL: Short Term Exposure Limit  
TLV: Threshold Limit Values  
TSCA: Toxic Substances Control Act