

# Material Safety Data Sheet

## **Section 1. Chemical Product and Company Identification**

Product Name: PHC 406 NP Permawick  
Synonyms: Hydro-cracked R&O lubricating oil with engineered fiber  
Product Use: Bearing Lubrication System

Supplier/ Manufacturer: **Permawick Company**  
**255 E. Brown Street**  
**Birmingham, Michigan 48009**  
**Tel:(248) 433-3500 Fax:(248) 433-1824**

### **Emergency Phone Numbers:**

Monday - Friday, 8 am – 4:30 p.m. (EST) (812) 376-0703  
Chemtrec 24 hr. : (800) 424-9300 (US and Canada)

### **Information Contacts:**

For technical information, contact your sales representative.

## **Section 2. Composition / Information on Ingredients**

### ***Criteria for Listing Components in the Composition Section:***

Carcinogens are listed at 0.1% or greater.

Components considered hazardous by OSHA are listed at 1.0 % or greater.

Non-hazardous components are listed at 3.0 % or greater.

\*This is not intended to be a complete compositional disclosure.\*

### ***Hazardous classification:***

|   | <b><u>CASRN</u></b> | <b><u>Percent (by wt.)</u></b> |
|---|---------------------|--------------------------------|
| 1. Mixture of hydro-cracked paraffinics | N/A                 | 75-85+%                        |
| 2. Permawick NP fiber                   | N/A                 | 10-20%                         |
| 2. Proprietary Additives                | Mixture             | < 5.0%                         |

See section 8 for Exposure Guidelines

## **Section 3. Hazards Identification**

### **\*\*\*\*Emergency Overview\*\*\*\***

This compound is not an acute or physical hazard under normal conditions of use. Under fire conditions there is a possibility of toxic phosphorous oxide vapors being released.

**Potential Health Effects, Signs and Symptoms of Exposure:**

**Inhalation:** Irritation possible. Fumes from heated material may cause irritation. Sprays or mists may be irritating to the upper respiratory tract.

**Ingestion:** May cause gastrointestinal irritation.

**Eye**

**Contact:** May cause tearing, reddening, or swelling.

**Skin**

**Contact:** Prolonged or repeated contact may result in defatting, and/or drying of the skin which may lead to skin irritation and dermatitis. Harmful if absorbed through the skin.

**Medical Conditions aggravated by exposure:** **None**

**Section 4. First Aid Measures**

**FIRST AID**

**Eye Contact:** Immediately flush eyes with plenty of water. If irritation develops or persists seek medical attention immediately.

**Ingestion:** Call a physician or poison control center immediately. Only induce vomiting at the instruction of a physician.

**Inhalation:** Immediately remove victim to fresh air. If victim has stopped breathing give artificial respiration, preferably by mouth to mouth. Get medical attention immediately.

**Skin**

**Contact:** Wash affected area immediately with soap and plenty of water. Remove contaminated clothing and wash clothing before reuse. If symptoms occur obtain medical attention immediately.

**Section 5. Fire Fighting Measures**

Flash Point : 243°C

Method used: ASTM D92

Auto-ignition Point: N/A (estimated)

Lower explosive limit: not available

Upper explosive limit: N/A

NFPA rating:  
none

**Other Flammable Properties:**

Can burn in a fire and form carbon dioxide and some carbon monoxide.

**Extinguishing Media:** Water spray or fog, foam, dry chemical or CO2.

**Fire Fighting Precautions and Procedure:**

MSDS PHC 406 NP  
REV. # 1  
REV. DATE: January 3<sup>rd</sup> 2006

Firefighters should wear self - contained breathing apparatus (MSHA / NIOSHA approved or equivalent) in the positive - pressure mode with full protective gear especially when there is the possibility of exposure to smoke, fumes or hazardous decomposition of products. Frothing may occur and may be quite violent. Water spray carefully applied has frequently been used with success in extinguishing such fires by causing the frothing to occur only on the surface and this foaming action blankets and extinguishes the fire (NFPA 325M - 1984). Containers can build up pressure if exposed to heat (fire). Cool with water spray.

## **Section 6. Accidental Release Measures**

### ***Spill or Release Procedures:***

Ventilate area. Absorb spill with inert material and place in appropriate chemical waste container. Obey any federal, state, and local laws and regulations. U.S. Coast Guard regulations require immediate reporting of spills that could reach any waterway including intermittent dry creeks. Do not flush into sewers discharging into domestic water systems or natural waterways. Use personal protective equipment (Sec.8). Spilled material will cause a slippery surface. Avoid trips and falls.

## **Section 7. Handling and Storage -**

### ***Handling:***

Thoroughly wash after handling. Use adequate ventilation and avoid breathing vapor or mist. Avoid contact with eyes, skin, and clothing.

### ***Storage:***

Keep container tightly closed when not in use and during transport.

## **Section 8. Exposure Controls / Personal Protection**

### **Exposure Guidelines:**

| <b><u>Component</u></b>                                      | <b><u>CAS#</u></b> | <b><u>Exposure Limits</u></b>  |
|--|--------------------|--|
| Mixture of hydro-cracked<br>Hydro-isomerised,<br>paraffinics | N/A                | OSHA PEL: 5 mg/m <sup>3</sup> (oil mist)<br>ACGIH TLV-TWA: 5 mg/m <sup>3</sup><br>(oil mist)<br>ACGIH TLV-STEL: 10 mg/m <sup>3</sup><br>(oil mist) |

### ***Engineering Controls:***

Adequate ventilation must be provided to control concentrations below exposure guidelines.

### ***Personal Protective Equipment:***

**Eye/Face Protection:** Use chemical splash goggles or other approved eye protection.

**Skin Protection:** Wear impermeable gloves to minimize skin contact.

**Respiratory Protection:** Where exposure is likely to exceed acceptable criteria, use NIOSH/OSHA approve respiratory equipment. Respirators should be selected based on the form and concentration of contaminant in air with OSHA concentration of contaminant in air and in accordance with OSHA (29 CFR 1910.134).

**Other Protective Equipment:** In order to identify additional Personal Protective Equipment requirements, the recommendation is made that a hazard assessment in accordance with the OSHA PPE Standard ( 29 CFR 1910.132) be conducted before product use.

## **Section 9. Physical and Chemical Properties**

|   |   |
|---|---|
| Boiling Point:                                | N/A                                       |
| Pour Point (oil only):                        | -27 °C (ASTM D-97)                        |
| Vapor Pressure:                               | NIL                                       |
| Vapor Density -<br>(Air = 1):                 | heavier than air                          |
| Specific Gravity:<br>@ 60 / 60 <sup>1</sup> F | 0.838                                     |
| Density:                                      | see specific gravity                      |
| pH:   | Not available                             |
| Viscosity (oil only)                          | 70-84cSt @ 40° C<br>8.3-10.1 Cst @ 100° C |
| Evaporation Rate:                             | slower than Butyl Acetate                 |
| Evaporation Loss<br>(Ethyl Ether = 1):        | 1000x slower                              |
| Solubility in water:                          | Insoluble                                 |
| Appearance<br>& color:                        | Light Grey, fibrous                       |
| Odor:   | mild odor                                 |
| % volatiles by<br>volume:                     | 0   |
| Volatility by<br>weight:                      | not available                             |

## **Section 10. Stability and Reactivity**

**Stability:** Stable under normal storage conditions.

**Hazardous Polymerization:** Will not occur during normal conditions

**Conditions to avoid:** Mechanical impact: none      Static discharge: none

**Material Incompatibility:** Avoid chlorine, fluorine, acids and other strong oxidizers

**Hazardous Decomposition Products:**

MSDS PHC 406 NP  
REV. # 1  
REV. DATE: January 3<sup>rd</sup> 2006

Carbon Dioxide, Carbon Monoxide, Aldehydes, Hydrogen sulfide, alkyl mercaptans, and sulfides. Under combustion conditions, oxides of the following elements will be formed: Phosphorus, Sulfur, .

## **Section 11. Toxicological Properties**

***Inhalation:*** No data available  
***Ingestion:*** No data available  
***Dermal:*** No data available  
***Mutagenicity:*** No data available

***Carcinogens:*** no NTP : no IARC: no

### ***Other Toxicological Information:***

The base oils in this product are severely solvent refined and/or severely hydro-treated. Two year mouse skin painting studies of similar oils showed no evidence of carcinogenic effects.

## **Section 12. Ecological Information**

***Ecological Fate:*** No specific aquatic data available

## **Section 13. Disposal Considerations**

***Disposal Method:*** All recovered material should be packaged, labeled, transported, and disposed or reclaimed in accordance with federal, state and local regulations. Incineration is the preferred method. Reclaim where possible.

## **Section 14. Transportation Information**

### ***U.S. Department of Transportation:***

DOT proper shipping name: not regulated  
DOT classification: not regulated

## **Section 15. Regulatory Information**

### ***U.S. Federal Regulations***

OSHA:

*Preparation of this document is in accordance with the MSDS requirements of the OSHA Hazard Communication Standard.*

SARA Section 311 / 312:

*Hazard classification: Hazardous by OSHA under 29 CFR 1910.1200 (d).*

SARA Section 302:

*Extremely hazardous substances : none*

SARA Section 313:

*This product contains the following substances subject to the reporting requirements of*

*Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:*

TSCA:

All functional components of this product are listed in the TSCA inventory .

CERCLA Hazardous Materials: *None reported*

OSHA Hazard Communication Standard:

*Contains a component listed by OSHA. Contains a component listed by ACGIH.*

RCRA:

*The unused product is not specifically listed by the E.P.A. as a hazardous waste (40 CFR, Part 261D).*

*The used product may be regulated by state or local laws.*

Clean Water Act:

*The material contains the following ingredients which is considered hazardous if spilled into navigable waters and therefore reportable to the national response center (1-800-424-8802)*

*Ingredient: Petroleum Hydrocarbon.*

*Reportable quantity: Film or sheen upon or discoloration of any water surface.*

**State Regulations -** None

## **Section 16. Other Information**

**HMIS Rating System:** Health : 1 Flammability: 1 Reactivity: 0

*Ratings key: 4 = Highest hazard , 0 = Lowest hazard, \* = Chronic Health Hazard*

**Revision summary:**

This is the first issue of this MSDS in the ANSI Z400.1 - 1993 format

Approval date : 1/10/97

Supersedes: 4/15/96

This information presented herein is believed to be factual as it has been derived from works and opinions of persons believed to be qualified experts; however, nothing contained in this information is to be taken as warranty or representation for which Permawick bears legal responsibility. Conditions of use and suitability of the product for particular uses are beyond our control. Any recommendations should be reviewed by the user in the specific context of the intended use to determine whether they are appropriate. Nothing is intended as a recommendation for uses which infringe valid patents or as extending license under valid patents.

ACGIH: American Conference of Governmental Industrial Hygienists

ANSI: American National Standards Institute

CASRN: Chemical Abstracts Service Registry Number

CERCLA: Comprehensive Emergency Response, Compensation and Liability Act

HMIS: Hazardous Material Identification System

IARC: International Agency for Resource and Conservation

NTP: National Toxicology Program

OSHA: Occupational Health and Safety Organization

PEL: OSHA Permissible Exposure Limit

RCRA: Resource Conservation and Recovery Act

SARA: Superfund Amendment Reauthorization Act

STEL: Short Term Exposure Limit

TLV: Threshold Limit Values

MSDS PHC 406 NP  
REV. # 1  
REV. DATE: January 3<sup>rd</sup> 2006  
TSCA: Toxic Substances Control Act  
TWA: Time Weighted Average