



An ISO9001 Certified Company

PD 77
 REV. # 1
 REV. DATE: 4/18/01

32400 Telegraph Road Bingham Farms, MI 48025
 Phone: 248-433-3500 • Fax: 248-433-1824
 Email: sales@permawick.com
 http://www.permawick.com

MINERAL OILS

77 OIL

PREMIUM CIRCULATING OIL

DESCRIPTION

PERMAWICK 77 OIL is formulated from carefully selected basestocks and special additives that provide oxidation and rust resistance. PERMAWICK 77 OIL provides long term dependable lubrication and resists high temperatures.

PRODUCT FEATURES

- Rust , corrosion and oxidation inhibited
- Long service life
- Excellent high temperature stability
- Excellent demulsibility
- Highly resistant to emulsification
- Resists foaming and readily eliminates entrained air

<u>PERFORMANCE TEST</u>	<u>ASTM METHOD</u>	<u>TYPICALS</u>
Gravity, API	D1298	29.3
Specific Gravity	D1298	0.880
Flash Point, Deg F	D92	441
Pour Point, Deg F	D97	-6
Viscosity, cst	D445	
100 Deg F		88.1
210 Deg F		9.76
40 Deg C		78.7
100 Deg F		9.5
Viscosity Index	D2270	97
Viscosity, SUS	D88	
100 Deg F		410
210 Deg F		58.5
Neutralization No., gm KOH/g	D664	0.06
Rust Prevention	D665A	pass
Rust Prevention	D665B	pass
Demulsibility, minutes	D1401	15
Oxidation Stability	D943	2000

The World Leader in Fractional Horsepower Motor Lubrication