



255 E. Brown Street, ste. 100, Birmingham, MI 48009
 Phone: 248-433-3500 • Fax: 248-433-1824
 Email: sales@permawick.com
<http://www.permawick.com>

PD P2AO 350PG
 REV. # 4
 REV. DATE: August 24, 2005

P2AO350PG PERMAGEL®

PAO BASED SYNTHETIC LUBRICANT FOR SINTERED METAL BEARINGS

DESCRIPTION & APPLICATIONS

P2AO350 PERMAGEL is especially developed for plastic compatibility for use in the fractional horsepower electric motor industry.

- Automotive applications: Wipers, window lifts, seat motors, blowers, radiator cooling fans, all small sintered metal bearing motors
- High-temp applications: pump motors requiring longer life, exhaust fans, tube axial fans, computer fans

PRODUCT FEATURES

- Long service life
- Corrosion and oxidation resistant
- Low evaporation
- Low pour and high VI indicate excellent low temperature fluidity characteristics
- Shear stable
- Excellent anti-wear performance
- Useful temperature range: -40 to 125°C

<u>PERFORMANCE TEST PERMAGEL</u>	<u>TEST METHOD</u>	<u>TYPICALS</u>
Base Oil		P2AO 350
Penetration (60 strokes, 25°C)	D217	NLGI #3
Color	Visual	Yellowish, Translucent
Drop Point	D566	Without
Density		0.99
Copper Corrosion @ 100°C	D4048	1b
Pounds/Gallon		8.25
Structure		Homogenous

<u>BASE OIL</u>	<u>TEST METHOD</u>	<u>TYPICALS</u>
Specific Gravity	D1298	0.8373
Flash Point, °F	D92	450
Pour Point, °F	D97	< -60
Viscosity, cSt	D445	
100 °F		75.78
210 °F		11.76
Viscosity Index	D2270	160
Neutralization No., mg KOH/g	D664	0.01
Evaporation Loss, wt. % 22hrs, 210°F	D972	0.4

The World Leader in Fractional Horsepower Motor Lubrication