



An ISO9001 Certified Company

PD P2AO 60
 REV. # 1
 REV. DATE: 4/18/01

32400 Telegraph Road Bingham Farms, MI 48025
 Phone: 248-433-3500 • Fax: 248-433-1824
 Email: sales@permawick.com
 http://www.permawick.com

POLYALPHAOLEFINS

P2AO60

SYNTHETIC PLASTIC COMPATIBLE IMPREGNATING FLUID

DESCRIPTION

PERMAWICK P2AO60 OIL was formulated to provide a plastic compatible lubricant for the fractional horsepower electric motor industry. With exceptionally low pour points and high viscosity index, these synthetics ensure low temperature pumpability and protection even in the harshest of low temperature conditions.

PERMAWICK P2AO60 OIL has excellent lubricating properties along with long term hydrolytic stability and increased chemical and thermal stability.

PRODUCT FEATURES

- Exceptional water separation
- Corrosion and oxidation resistant
- Soluble in conventional oils
- Long service life means longer lubricant change intervals
- Less downtime

<u>PERFORMANCE TESTS</u>	<u>ASTM METHOD</u>	<u>TYPICALS</u>
ISO VG	D2422	10
Gravity, API	D1298	42.98
Specific Gravity	D1298	0.8112
Color	D1500	0.5
Flash Point, Deg F	D92	320
Fire Point, Deg F	D92	355
Pour Point, Deg F	D97	-85
Viscosity, cSt	D445	
100 Deg F		10.7
210 Deg F		2.76
Viscosity Index	D2270	116
Viscosity, SUS	D88	
100 Deg F		61
210 Deg F		35.2
Neutralization No. mg KOH/g	D664	0.01
Copper Strip Corrosion	D130	
3 hours @ 212 Deg F		1A

The World Leader in Fractional Horsepower Motor Lubrication