



255 East Brown Street, Ste 100, Birmingham, MI, 48009
 Phone: 248-433-3500 • Fax: 248-433-1824
 Email: sales@permawick.com
<http://www.permawick.com>

PWS 115
 REV. # 1
 REV. DATE: Sept 23 2008

PWS115 Oil

DESCRIPTION

PERMAWICK PWS OILS have been formulated especially for **extremely high temperature** applications. In addition these oils provide protection against oxidation, corrosion and wear. PERMAWICK PWS115 oil was designed to be impregnated into sintered metal bearings where it could be utilized at temperatures up to 250°C PWS195 also provides excellent chemical compatibility, low flammability and low toxicity.

PRODUCT FEATURES

- Extremely high temp applications not tolerated by Esters or PAO's
- Very long life
- Low evaporation
- Shear stable
- Low pour points and high viscosity index indicate excellent low temperature flow properties and therefore continued protection during periods of both low and high temperature operation.
- Cost effective choice to other higher priced high temperature oils
- Life expectancy at 250°C is 1200 to 1500hrs

<u>Performance Test</u>	<u>ASTM Method</u>	<u>Typicals</u>
Specific gravity	D1298	0.99
Color	D1500	Clear and colorless
Flash Point, °C	D92	280
Ignition temp °C	D92	484
Pour Point, °C	D97	-70
Viscosity, cSt. 25°C	D445	115
100°C		31
Viscosity Index	D2270	386

The World Leader in Fractional Horsepower Motor Lubrication